




Double row spherical roller bearings with cylindrical and tapered bore




EW33J



W33M



EKW33J



| | |
|--|-------------|
| Bearing Designation with Cylindrical Bore | 22206EW33J |
| Bearing Designation with Tapered Bore (1:12) | 22206EKW33J |

Dimensions (mm)

| | |
|--------------------|----|
| d | 30 |
| D | 62 |
| B | 20 |
| r _s min | 1 |

Abutment and Fillet Dimensions (mm)

| | |
|--------------------|------|
| d _a min | 35,6 |
| D _a max | 56,4 |
| r _a max | 1 |

Basic Load Rating (kN)

| | |
|----------------|-------|
| C | 61,12 |
| C ⁰ | 65,86 |

Limiting Speed for Lubrication (min⁻¹)

| | |
|--------|------|
| Grease | 7500 |
| Oil | 9000 |

| | |
|-----------------|-------|
| Weight [kg] | 0,270 |
| Weight - K [kg] | 0,260 |

Corresponding

| | |
|-------------------|-------|
| Adapter Sleeve | H306 |
| Withdrawal Sleeve | AH306 |
| Withdrawal Nut | KM7 |

Coefficients

| | |
|----------------|------|
| e | 0,31 |
| Y ₁ | 2,1 |
| Y ₂ | 3,3 |
| Y ₃ | 2,1 |

Tolerance Class

| Tolerance Class | Inner Ring | | | | | | | | | |
|-----------------|------------------|-----|-----------------|-----|-------|-----------|----------|---------------|------|----------|
| | Cylindrical Bore | | | | | | | | | |
| | Δ_{dmp} | | V_{dp} | | | V_{dmp} | K_{ia} | Δ_{BS} | | V_{BS} |
| | | | Diameter Series | | | | | | | |
| | | | 7,8,9 | 0,1 | 2,3,4 | | | | | |
| max | min | max | max | max | max | max | min | max | | |
| μm | | | | | | | | | | |
| P0 | 0 | -10 | 13 | 10 | 8 | 8 | 13 | 0 | -120 | 20 |
| P6 | 0 | -8 | 10 | 8 | 6 | 6 | 8 | 0 | -120 | 20 |

| Tolerance Class | Inner Ring | | | | | | | | | | | | | | |
|-----------------|-------------------|---|--------------------------------|---|---------------|-------------------|---|--------------------------------|---|---------------|-----|-----|-----|-----|-----|
| | Tapered Bore 1:12 | | | | | Tapered Bore 1:30 | | | | | | | | | |
| | Δ_{dmp} | | $\Delta_{d1mp} - \Delta_{dmp}$ | | $V_{dp}^{1)}$ | Δ_{dmp} | | $\Delta_{d1mp} - \Delta_{dmp}$ | | $V_{dp}^{1)}$ | | | | | |
| | | | | | | | | | | | max | min | max | min | max |
| | | | | | | | | | | | max | min | max | min | max |
| μm | | | | | | | | | | | | | | | |
| P0 - P6 | 21 | 0 | 21 | 0 | 13 | - | - | - | - | - | | | | | |

| Tolerance Class | Outer Ring | | | | | | | | | |
|-----------------|----------------|-----|-----------------|-----|-------|--------------------------------------|-----------|----------|---|--|
| | Δ_{Dmp} | | V_{Dp} | | | bearings ²⁾ with seals | V_{Dmp} | K_{ea} | Δ_{CS}, V_{CS} | |
| | | | Diameter Series | | | | | | | |
| | | | 7,8,9 | 0,1 | 2,3,4 | | | | | |
| | max | min | max | max | max | max | max | | | |
| μm | | | | | | | | | | |
| P0 | 0 | -13 | 16 | 13 | 10 | 20 | 10 | 25 | Corresponds to Δ_{BS}, V_{BS} of the same bearing inner ring | |
| P6 | 0 | -11 | 14 | 11 | 8 | 16 | 8 | 13 | | |

1) Valid in any bore radial plane

2) P0 - Valid only for bearings in diameter series 2, 3 and 4 * P6 - Valid only for bearings in diameter series 0, 1, 2, 3 and 4

Radial Clearance - Cylindrical Bore

| C2 | | normal | | C3 | | C4 | | C5 | |
|---------|-----|--------|-----|-----|-----|-----|-----|-----|-----|
| min | max | min | max | min | max | min | max | min | max |
| μm | | | | | | | | | |
| 15 | 30 | 30 | 45 | 45 | 60 | 60 | 80 | 80 | 100 |

Radial Clearance - Tapered Bore

| C2 | | normal | | C3 | | C4 | | C5 | |
|---------|-----|--------|-----|-----|-----|-----|-----|-----|-----|
| min | max | min | max | min | max | min | max | min | max |
| μm | | | | | | | | | |
| 25 | 35 | 35 | 50 | 50 | 65 | 65 | 85 | 85 | 105 |

Tolerance Symbols and Their Meaning

| | | | |
|-----------------|--|----------------|---|
| d | nominal bore diameter | H_4 | rated height of spherical-roller bearing |
| d_1 | nominal diameter of larger theoretical tapered bore diameter | Δ_{Bs} | inner ring single width deviation |
| d_2 | nominal diameter of the shaft washer of double direction thrust bearings | Δ_{Cs} | outer ring single width deviation |
| Δ_{ds} | deviation of single bore diameter from nominal | Δ_{Is} | bearing single width deviation (total) |
| Δ_{dmp} | mean cylindrical bore diameter deviation in single radial plane (for tapered bore Δ_{dmp} is valid for theoretical bore diameter) | Δ_{T1s} | cone sub-unit effective width deviation |
| Δ_{d1mp} | deviation of mean larger theoretical diameter of tapered bore | Δ_{T2s} | cup sub-unit effective width deviation |
| Δ_{d2mp} | mean shaft washer bore diameter deviation of double direction thrust bearings in single radial plane | Δ_{Hs} | height deviation of single direction axial bearings from nominal value |
| V_{dp} | single bore diameter variation in single radial plane | Δ_{H1s} | height deviation of single direction axial ball bearings with sphered housing washer from nominal value |
| V_{dmp} | mean cylindrical bore diameter variation | Δ_{H2s} | height deviation of double direction axial bearings from nominal value |
| V_{d2p} | shaft washer bore diameter variation of double direction thrust bearings in single radial plane | Δ_{H3s} | height deviation of double direction axial ball bearings with sphered housing washer from nominal value |
| D | nominal outside diameter | Δ_{H4s} | height deviation of axial spherical-roller bearing from the rated value |
| Δ_{Ds} | deviation of single outside diameter from the nominal dimension | C | outer ring nominal width |
| Δ_{Dmp} | mean outside cylindrical surface diameter deviation in single plane | V_{Bs} | inner ring single width variation |
| V_{Dp} | single outside cylindrical surface diameter variation in single radial plane | V_{Cs} | outer ring single width variation |
| V_{Dmp} | mean outside cylindrical surface diameter variation | K^{ia} | radial runout of assembled bearing inner ring |
| B | inner ring nominal width | K^{ea} | radial runout of assembled bearing outer ring |
| T | total nominal width of tapered roller bearings | S_t^{ea} | shaft washer raceway axial runout |
| T_1 | nominal effective width of cup sub-unit | S_t^e | housing washer raceway axial runout |
| T_2 | nominal effective width of cone sub-unit | S_{ia}^e | inner ring flat seat face axial runout of assembled bearing |
| H | rated width of unidirectional axial bearing | S_{ea}^e | outer ring flat seat face axial runout of assembled bearing |
| H_1 | rated height of unidirectional ball axial bearing including the body ring | S_d^{ea} | flat seat face axial runout |
| H_2 | rated height of bidirectional axial bearing | S_D | runout of outside cylindrical surface towards outer ring face |
| H_3 | rated height of bidirectional axial ball bearing including body rings | S_s | runout of supporting face towards seat face for single row tapered roller bearings |